

SYSTIMAX® M2000 U/UTP Modular Patch Panel



Supports copper and fiber connectors

The SYSTIMAX® M2000 Modular Patch Panel is a 1U 24 Port Patch Panel. It is designed for M-series outlets that can be configured for copper, fiber, or both. The M2000-1U panel mounts in a 19-inch (483 mm) rack with universal hole spacing.

The M2000-1U Panel includes M2000 Cable Organizers. The M2000 Cable Organizer is a molded plastic design that is mounted to each 6-port bezel. The M2000 24 port 1U panel includes 4 cable organizers. The six 4-pair cables from each bezel are routed and positioned to the cable organizer. Cable ties are included to secure the cables.

The M2000-1U includes a label sheet and clear label holders. A label area is provided to the left of each port. Port designations can be printed on the label sheet and individual port labels are trimmed from the label sheet and placed in the label area and secured by the clear label holder. If adhesive labeling is desired, adhesive labels can be applied to the label holder. The M2000-1U Panel now includes M2000 Cable Organizers. The M2000 Cable Organizer is a molded plastic design that is snapped into each 6-port bezel. The 24 port 1U panel includes 4 cable organizers.

Also available and sold separately are M2000 1U Patch Cord Managers. These patch cord managers are metal rings that mount to the front of the panel. 5 patch cord managers are used for each 24 port 1U panel. The M2000 1U Patch Cord Manager Kit is a package of 5 patch cord managers.

- Supports PowerSUM, GigaSPEED® XL and GigaSPEED® X10D installations
- Available in 24-port configuration
- Labeling and identification for each port

Product Specifications



M2000-24 1U

Material ID: 760049932

M2000 U/UTP Modular Patch Panel 1U, 24 port

CHARACTERISTICS

Dimensions

Depth	30.48 mm 1.20 in
Height	44.45 mm 1.75 in
Width	482.60 mm 19.00 in

Electrical Specifications

ANSI/TIA Category	3 5 5e 6 6A
-------------------	---------------------

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	cUL UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Brand	SYSTIMAX®
Product Type	Panel Panel, modular
Total Ports, quantity	24
Color	Black
Package, quantity	1
Rack Type	EIA 19 in
Rack Units	1

Mechanical Specifications

Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
---------------	---

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2002/95/EC	Compliant
ISO 9001:2000	Compliant

Product Specifications

M2000-24 1U - Material ID: 760049932

